



Sialex®Ring Specifications

size		max. water flow (m ³ /h)			A (in mm)	B (in mm)	C (in mm)	t (in mm)
inch	DN	Classic	Industrial	Optimum				
1/2"	15	1,0	4,0	40,0*	24,0	76,0	25,0	30,0
3/4"	20	1,0	4,0	40,0*	31,0	83,0	25,0	30,0
1"	25	1,0	4,0	40,0*	37,0	89,0	25,0	30,0
1 1/4"	32	1,0	4,0	40,0*	46,0	98,0	25,0	30,0
1 1/2"	40	1,5	8,0	60,0*	51,0	103,0	25,0	30,0
2"	50	1,5	8,0	60,0*	63,0	125,0	30,0	30,0
2 1/2"	65	XXX	16,0	80,0*	75,0	137,0	30,0	30,0
3"	80	XXX	16,0	110,0*	91,0	153,0	30,0	40,0
4"	100	XXX	30,0*	250,0*	120,0	192,0	35,0	40,0
5"	125	XXX	30,0*	400,0*	150,0	222,0	35,0	40,0
6"	150	XXX	60,0*	550,0*	180,0	252,0	35,0	40,0
8"	200	XXX	60,0*	650,0*	230,0	312,0	40,0	40,0
10"	250	XXX	80,0*	800,0*	285,0	367,0	40,0	60,0
12"	300	XXX	80,0*	1000,0*	335,0	417,0	40,0	60,0

* Sialex®SynRing combination (consisting of two Sialex®Rings)